

MasterCut

Traversing speed Z-axis clearances 15 m/min 200 mm XY positioning accuracy ± 0,05 mm (per Meter at 20° C)

XY repeatability accuracy ± 0,03 mm (per Meter at 20° C)

- Welded, stainless steel aluminum and stainless steel machine basin
- ► Heavy-duty supports for workpieces up to 1,000 kg/m²
- Recirculating ball bearing guide X and Y axes
- STM SmartCut waterjet cutting software
- Ergonomic control panel including rollers
- STM Edge Tracker Position laser
- Brushless servo motors
- Precision wedge shoes
- CNC control
- CNC Z axis



Optionen:

- ▶ Manual cutting valve rotary holder for bevel cuts up to 48°
- Sedimentation tank with pressure bag filter for overflow
- Additional cutting valves on own Z-axis or cantilever
- ► STM BasicClean or STM OneClean flushing systems
- ► STM TAC 12° bevel cut compensation cutting head
- Abrasive storage tank for 450 kg or 1,650 kg
- Automatic water level control
- Collecting grid for small parts
- STM lance flushing system
- Drilling spindle pneumatic

STM Waterjet Group partnership, precision and performance

STM WATERJET GMBH

STM WATERJET AG **SWITZERLAND**

Kreuzmatte 1e W: www.stm-waterjet.ch E: info.ch@stm-waterjet.com