

MicroCut 4.0

| | | | |
|-------------------|----------|--------------------------|---------------------------------|
| Traversing speed: | 10 m/min | XY repeatability: | ± 0,0025 mm (per meter at 20°C) |
| Z-axis clearance: | 100 mm | XY positioning accuracy: | ± 0,0025 mm (per meter at 20°C) |

Ausstattung:

- ▶ Stainless steel catch basin with integrated rinsing device
- ▶ Pressure conveying system integrated in machine frame
- ▶ Protective enclosure with automatic door
- ▶ STM SmartCut waterjet cutting software
- ▶ Abrasive hopper 100 kg with minihopper
- ▶ Direct absolute measuring system
- ▶ STM Edge Tracker position laser
- ▶ Machine frame with granite bed
- ▶ Precision clamping frame
- ▶ Ergonomic control panel
- ▶ Linear motor drives
- ▶ CNC control NUM



Optionen:

- ▶ STM BasicClean or STM OneClen washout systems
- ▶ STM TAC 12° skew cut compensation cutting head
- ▶ Settling tank with pressure bag filter for overflow
- ▶ Automatic water level control
- ▶ Drilling spindle pneumatic

STM Waterjet Group
partnership, precision and performance

STM WATERJET GMBH
AUSTRIA

Gewerbegebiet Gasthof Süd 178
5531 Eben im Pongau, Austria
T: +43 6458 200 14-0
W: www.stm-waterjet.com
E: info@stm-waterjet.com

STM WATERJET AG
SWITZERLAND

Kreuzmatte 1e
6260 Reiden, Switzerland
T: +41 62 772 44 44
W: www.stm-waterjet.ch
E: info.ch@stm-waterjet.com